



The Lusso Collection powered by ARRAY from Visionaire Lighting can elegantly compliment the daytime architecture of your space, while providing nighttime illumination that is up to task and equally as elegant. The collection consists of a wall sconce, bollard, single or twin arm post top and a beautiful pole mount. Available in two housings sizes and lumen packages up to 55,000 lumens thanks to our performance ARRAY LED platform. Scale and design creativity has no limits for any application.

Lusso Medium Post Top w/ Serenity Lens



Key Features

- Cast aluminum housing
- IP65 Housing and LED optical assembly
- 400 W Replacement
- 5 Specification Grade low glare optics
- 5,000 – 17,000 lumen packages
- 52 – 200 wattage range
- 120-277 universal Drivers, 347 & 480 voltage drivers
- 10KV Surge Protector
- 90% Power Factor
- 10 Year Electrical Warranty
- PangeaLink compatible
- Cantilever and Yoke Mount Design
- Mounts over 3" OD tenon
- 3, 5 and 7 Photocell receptacles
- 0-10V Dimming driver
- Title 24 Compliant Motion Sensor

LUSSO ARRAY M-PT Serenity Lens LED Specifications



Project Name: _____

Catalog Number: _____

Type: _____

Contemporary design meets the new generation of LED green technology in this stunning luminaire, the **Lusso Array**. The Lusso Array series provides over fifty percent energy savings over traditional HID light sources; and offers excellent beam control and LED life beyond 100,000 hours for 1400 milliamp systems. The Lusso Array is offered in ten optical distributions.

The Lusso Array's fully-sealed housing features an exceptionally well-designed thermal management system that provides superior heat dissipation.

The Lusso Array fixture is built with cast aluminum.

The **Lusso Array** is the perfect compliment to any university campus, business park, or walkway project where contemporary, architectural design is desired.

Ordering Information

MODEL	OPTICS	LUMENS	KELVIN	VOLTAGE	MOUNTING	FINISH	SERENITY LENS	OPTIONS
LSO-M	T1 Type 1	5L	3K 3000K	UNV 120-277V	PTS Post Top Single Arm	BK Black	LDL Lightly Diffused Lens	PCR-120 Photocell & Receptacle
	T2 Type 2	8L	4K 4000K	8 347V		SBK Smooth Black	HDL High Diffused Lens	PCR-208 Photocell & Receptacle
	T3L Type 3 Long	11L	5K 5000K	5 480V		PTD Post Top Double Arm	BZ Bronze	PCR-240 Photocell & Receptacle
	T4L Type 4 Long	14L				The Lusso Medium Post Top will slip over a 3" O.D. X 4" Tall tenon	GP Graphite	PCR-277 Photocell & Receptacle
	T5LS Type 5 Long Square	17L					GY Grey	PCR-480 Photocell & Receptacle
					SL Silver Metallic	PER 3 Pin Photo Receptacle w/shorting cap	5PINPER 5 Pin Photo Receptacle w/shorting cap Requires Dimming Driver	
					WH White	7PINPER 7 Pin Photo Receptacle w/shorting cap Requires Dimming Driver	DIM 0-10v Dimming Driver	
					SWH Smooth White	WSC-8 Motion Sensor 8' Mounting Height	WSC-20 Motion Sensor 9-20' Mounting Height	WSC-40 Motion Sensor 21-40' Mounting Height
					FG Forest Green	The WSC option will require (1) PSIR 100 remote for programming		
					VD Verdigris Green	VVC Visionaire Wireless Controls Consult Factory	ROT-R Rotated Optics Right Side	ROT-L Rotated Optics Left Side
					CC Custom Color			