



***The Lusso Collection powered by ARRAY from Visionaire Lighting can elegantly compliment the daytime architecture of your space, while providing nighttime illumination that is up to task and equally as elegant. The collection consists of a wall sconce, bollard, single or twin arm post top and a beautiful pole mount. Available in two housings sizes and lumen packages up to 55,000 lumens thanks to our performance ARRAY LED platform. Scale and design creativity has no limits for any application.***

## ***Lusso Bollard***



### ***Key Features***

- *Cast aluminum housing*
- *IP65 Housing and LED optical assembly*
- *6 Specification Grade low glare optics*
- *Serenity High and Low Diffused lens*
- *1,000 - 5,000 lumen packages*
- *13 45 wattage range*
- *120-277 universal Drivers*
- *10KV Surge Protector*
- *90% Power Factor*
- *5 Year Electrical Warranty*
- *Button Style Photocell*
- *0-10V Dimming driver*
- *PangeaLink compatible*



# LUSSO Bollard LED Specifications



Project Name:

Catalog Number:

Type:

The **Lusso Bollard LED** Series continues the unique contemporary design inspired by the sleek styling of the Lusso family. Separating the Driver(s) from the individual cast aluminum LED engines: optimize the life of the LEDs and the Driver(s); and maximizes the lumen output of the fixture.

Six optical distribution patterns are available. Choose between 3K, 4K or 5K Kelvin temperature of the LED's.

A durable polyester powdercoat finish is guaranteed for five years; and is available in standard or custom colors.

The **Lusso Bollard LED** Series is an exceptional choice for low level lighting applications.

## Ordering Information

MODEL	HEIGHT	OPTICS	SOURCE	CURRENT	KELVIN	VOLTAGE	MOUNTING	FINISH	OPTIONS
LSO-B	S36 Straight 36"	T1 Type 1	20LC	1 175mA	3K 3000K	UNV 120-277V	AB Anchor Base	BK Black	PC-120 Button Type Photocell
		T2 Type 2		3 350mA	4K 4000K			SBK Smooth Black	PC-208 Button Type Photocell
	T3 Type 3	5 530mA		5K 5000K	BZ Bronze			PC-240 Button Type Photocell	
	T4 Type 4	7 700mA		GP Graphite	PC-277 Button Type Photocell				
	T5 Type 5			GY Grey					
	T5W Type 5 Wide			SL Silver Metallic				DIM 0-10v Dimming Driver	
	S41 Straight 41"							WH White	LDL Lightly Diffused Lens
								SWH Smooth White	HDL High Diffused Lens
								FG Forest Green	VD Verdigris Green
								CC Custom Color	