

BLX-II LED Specifications

Area - Site - Commercial - Outdoor



BLX-II-4 Bolt On Arm Mount Shown

The BOW LX II LED Series elevates the signature contemporary design of the BOW family of luminaires, blending architectural styling with exceptional performance for today's most demanding area-lighting applications. Its innovative construction separates the robust extruded-aluminum driver housing from the individual die-cast aluminum linear LED engines—maximizing thermal management, extending component life, and delivering superior lumen output.

An adjustable knuckle with up to 50° of vertical aiming ensures precise light placement, giving designers and end users complete control over site illumination.

Each linear LED engine contains 32 high-performance LEDs, configurable up to a total of 256 LEDs per fixture. Select from 2700K, 3000K, 3500K, 4000K, or 5000K color temperatures and 70, 80, or 90 CRI options to achieve the ideal visual environment. With seventeen precision-engineered optical distributions, the BOW LX II delivers light exactly where it is needed—enhancing safety, visibility, and overall site aesthetics.

Engineered for large-scale performance, the BOW LX II provides up to 126,000 lumens with wattage packages up to 966 watts, achieving an impressive 141 lumens per watt. Integrated lighting controls further optimize efficiency, flexibility, and long-term energy savings.

Project Name:

Catalog Number:

Type:

Date:

Location:

A durable polyester powder-coat finish, guaranteed for five years, is available in both standard and custom colors to complement any project's design palette.

The BOW LX II LED Series is an outstanding solution for auto dealerships, retail centers, commercial parking environments, and general area-lighting applications—delivering unmatched performance, aiming flexibility, and architectural appeal.

MODEL	OPTICS		LEDs	CURRENT	CCT
BLX-II-3	T1 Type 1	T5 Type 5	96LD	3 350mA	27K7 27K8 27K9 2700K 70, 80, & 90 CRI
BLX-II-4	T2 Type 2	T5W Type 5 Wide	128LD	5 530mA	30K7 30K8 30K9 3000K 70, 80, & 90 CRI
BLX-II-6	T3 Type 3	T5WW Type 5 Extra Wide	192LD	7 700mA	35K7 35K8 35K9 3500K 70, 80, & 90 CRI
BLX-II-8	T3R Type 3 Round	T5LG Type 5 Low Glare	256LD	10 1050mA	40K7 40K8 40K9 4000K 70, 80, & 90 CRI
	T3W Type 3 Wide	FN Flood Narrow		12 1200mA	50K7 50K8 50K9 5000K 70, 80, & 90 CRI
	T3LG Type 3 Low Glare	FM Flood Medium			
	T4 Type 4	FW Flood Wide			
	T4A Type 4 Automotive				
	T4FT Type 4 Forward Throw				
	T4LG Type 4 Low Glare				

VOLTAGE	MOUNTING	FINISH	CONTROL OPTIONS	SHIELD OPTIONS	OPTIONS
UNV 120-277V	PT Post Top	WM Wall Mount BLX-III-3 & BLX-III-4 Only	BZ Bronze	CLC Backside cutoff shield	RPP-3" RPP-4" RPP-5" Round Pole Plate Adaptor
8 347V	MA Mast Arm Fitter	AWM Adjustable Wall Mount BLX-III-3 & BLX-III-4 Only	BK Black	RCLS Rightside cutoff shield	DS Decorative Shroud
5 480V	KM Knuckle Mount	BAWP Bolt-On Arm Wall Plate *BLX-III-3 & BLX-III-4 only	GY Grey	LCLS Leftside cutoff shield	ROT-R Rotated Optics Right Side
	BOA Bolt-On Arm	BAWP-XL Bolt-On Arm Wall Plate-XL *BLX-III-6 & BLX-III-8 only	SBK Smooth Black	BHS House shield	ROT-L Rotated Optics Left Side
	AM Arm Mount Extended arm is needed for the BLX-III-6 & BLX-III-8 in D9, T9, T120 & QD configurations * extended arm sold separately		WH White		UPMA-S Universal Square Pole Mount Adaptor * Not available with BLX-II-8
	TM Trunnion Mount		SWH Smooth White		UPMA-R Universal Round Pole Mount Adaptor * Not available with BLX-II-8
			GP Graphite	WSP-8 WSP-20 WSP-40 8" Mounting Height 9-20" Mounting Height 21-40" Mounting Height	BBG Bird Spikes
			GY Grey	WSC-8 WSC-20 WSC-40 8" Mounting Height 9-20" Mounting Height 21-40" Mounting Height	BAA Buy America(n) Act Compliant
			SL Silver Metallic	* The WSC option will require (1) FSIR 100 remote for programming	BABA Build America Buy American
			ZFP Zinc-Free Primer Coat	TL7 7-PIN Twist Lock Wireless Control	
			CC Custom Color	Z10 or Z18 Zhaga 4 Pin Receptacle	
				VWC Visionaire Wireless Control	

Housing

- The LED light engines are constructed of heavy-duty, die-cast aluminum, with external heat radiating fins.

Driver Compartment

- The separate driver housing is constructed of extruded aluminum, with vented cast aluminum end covers and stainless steel fasteners; for easy access to the LED driver(s); allowing for cooler operation and longer driver life. One-piece gasketing is utilized throughout the fixture for weather tight operation.

Thermal Management

- The BOW LX II Series provides excellent overall thermal management by maximizing the fixture's heat sink capabilities. This enables the BOW LX II Series to withstand higher ambient temperatures and drive currents without degrading LED life.
- The L70 test determines the point in an LEDs life when it reaches 70 percent of its initial output. The BOW LX II Series LEDs have been determined to last a minimum of 100,000 hours in 25°C environments when driven at 350 mA.

Optical System

- The highest lumen output, LEDs are utilized in the BOW LX II Series. Available with 17 IES distribution patterns. LED light engines come in multiples of 32 LEDs.
- CRI values are 70, 80 or 90.
- CCT values are 2700K, 3000K, 3500K, 4000K, 5000K

Quali-Guard® Finish

- The finish is a Quali-Guard® textured, chemically pretreated through a multiple-stage washer, electrostatically applied, thermoset polyester powder coat finish, with a minimum of 3-5 mils thickness. Finish is oven-baked at 400 °F to promote maximum adherence and finish hardness.
- All finishes are available in standard and custom colors.
- Optional Zinc-Free Primer - Recommended within three miles of the ocean
- Finish is guaranteed for five (5) years.

Mounting

- An adjustable knuckle slip fits over a 2 3/8" Tenon, and allows for up to 50° degrees of vertical adjustment in 10° degree increments from horizontal, as well as full side to side adjustment with the knuckle mount.
- The Bolt -On Arm (BOA) utilizes a 2 piece cleat system for easy installation. A Round Pole Plate Adaptor (RPP) is required for mounting to round poles.
- Mast Arm Fitter fits over a 2 3/8" tenon.
- Post Top fits over a 2 3/8" tenon and is adjustable up to 45°.
- Trunnion Mount is adjustable up to 50°
- Adjustable Wall Mount
- Bolt-On Arm Wall Plate
- Bolt-On Arm Wall Plate-XL

Electrical Assembly

- The BOW LX II Series is supplied with a choice of 350, 530, 700, 1050 or 1200 mA high-performance LED drivers, that accept 120v thru 480v, 50 Hz to 60 Hz, input.
- Rated for -40 °C to +55 °C operations.
- Power factor of 90%.
- THD less than or equal to 20%
- 20 kV surge protector supplied as standard.
- 0-10v Dimming Driver supplied as standard.

Warranty

- Five (5) year Limited Warranty on entire system, including finish. For full warranty information, please visit VisionaireLighting.com.

Options


- Button Type Photocell
- Photocell & Receptacle
- Round pole plate adaptor
- Motion Sensor
- Pole Mounted Motion Sensor
- Universal Pole Mount Adaptor (BLX-II-3, BLX-II-4 & BLX-II-6 Only)
- Decorative Shroud
- Cut-Off Louver Shield
- Zhaga 4 Pin Receptacle

Listings







- BOW LX II Series is UL listed, suitable for wet locations
- Meets ANSI C136.31-2010 3G Vibration Standards
- Powder Coated Tough™
- IP-66 Rated
- IDA Certification
- Pangealink



3000K or lower must be selected with a fixed mount for IDA certification.
Fixed mount must be selected for IDA dark sky certification.

Photometric Optical Summary**Dimensions**


Post Top		Mast Arm		Knuckle Mount		Bolt-On Arm		Trunnion		Adjustable Wall Mount	
Width:	BLX-II-3 15"	Width:	BLX-II-3 15"	Width:	BLX-II-3 15"	Width:	BLX-II-3 15"	Width:	BLX-II-3 15"	Width:	BLX-II-3 15"
	BLX-II-4 17"		BLX-II-4 17"		BLX-II-4 17"		BLX-II-4 17"		BLX-II-4 17"		BLX-II-4 17"
	BLX-II-6 28"		BLX-II-6 28"		BLX-II-6 28"		BLX-II-6 28"		BLX-II-6 28"		BLX-II-6 28"
	BLX-II-8 33"		BLX-II-8 33"		BLX-II-8 33"		BLX-II-8 33"		BLX-II-8 33"		BLX-II-8 33"
Depth:	BLX-II-3 36"	Depth:	BLX-II-3 36"	Depth:	BLX-II-3 37"	Depth:	BLX-II-3 34"	Depth:	BLX-II-3 33"	Depth:	BLX-II-3 33"
	BLX-II-4 36"		BLX-II-4 36"		BLX-II-4 37"		BLX-II-4 34"		BLX-II-4 33"		BLX-II-4 33"
	BLX-II-6 36"		BLX-II-6 36"		BLX-II-6 37"		BLX-II-6 34"		BLX-II-6 33"		BLX-II-6 33"
	BLX-II-8 36"		BLX-II-8 36"		BLX-II-8 37"		BLX-II-8 34"		BLX-II-8 33"		BLX-II-8 33"
Height:	BLX-II-3 6"	Height:	BLX-II-3 5"	Height:	BLX-II-3 5"	Height:	BLX-II-3 5"/9"	Height:	BLX-II-3 5"	Height:	BLX-II-3 5"/8"
	BLX-II-4 6"		BLX-II-4 5"		BLX-II-4 5"		BLX-II-4 5"/9"		BLX-II-4 5"		BLX-II-4 5"/8"
	BLX-II-6 6"		BLX-II-6 5"		BLX-II-6 5"		BLX-II-6 5"/9"		BLX-II-6 5"		BLX-II-6 5"/8"
	BLX-II-8 6"		BLX-II-8 5"		BLX-II-8 5"		BLX-II-8 5"/9"		BLX-II-8 5"		BLX-II-8 5"/8"

Post Top**Mast Arm****Knuckle Mount****Bolt-On Arm****Trunnion Mount****Adjustable Wall Mount**

BLX-II - ELECTRICAL LOAD (A)							
Ordering Nomenclature	System Watts	120	208	240	277	347	480
BLX-II-3-T5-96LD-3	99	0.82	0.47	0.41	0.36	0.28	0.21
BLX-II-3-T5-96LD-5	152	1.27	0.73	0.63	0.55	0.44	0.32
BLX-II-3-T5-96LD-7	204	1.70	0.98	0.85	0.74	0.59	0.42
BLX-II-3-T5-96LD-10	314	2.62	1.51	1.31	1.14	0.91	0.66
BLX-II-3-T5-96LD-12	362	3.02	1.74	1.51	1.31	1.04	0.75
BLX-II-4-T5-128LD-3	132	1.10	0.63	0.55	0.47	0.38	0.27
BLX-II-4-T5-128LD-5	203	1.69	0.98	0.85	0.73	0.58	0.42
BLX-II-4-T5-128LD-7	272	2.27	1.31	1.13	0.98	0.78	0.57
BLX-II-4-T5-128LD-10	419	3.49	2.02	1.75	1.51	1.21	0.87
BLX-II-4-T5-128LD-12	483	4.03	2.32	2.01	1.74	1.39	1.01
BLX-II-6-T5-192LD-3	197	1.64	0.95	0.82	0.71	0.57	0.41
BLX-II-6-T5-192LD-5	304	2.53	1.46	1.27	1.10	0.88	0.63
BLX-II-6-T5-192LD-7	408	3.40	1.96	1.70	1.47	1.17	0.85
BLX-II-6-T5-192LD-10	629	5.24	3.02	2.62	2.27	1.81	1.31
BLX-II-6-T5-192LD-12	725	6.04	3.48	3.02	2.62	2.09	1.51
BLX-II-8-T5-256LD-3	263	2.19	1.26	1.10	0.95	0.76	0.55
BLX-II-8-T5-256LD-5	406	3.38	1.95	1.69	1.46	1.17	0.84
BLX-II-8-T5-256LD-7	544	4.53	2.61	2.26	1.96	1.57	1.13
BLX-II-8-T5-256LD-10	838	6.99	4.03	3.49	3.03	2.42	1.75
BLX-II-8-T5-256LD-12	966	8.05	4.64	4.02	3.49	2.78	2.01


BLX-II EPA Data				
Tilt Deg.	BLX-II-3	BLX-II-4	BLX-II-6	BLX-II-8
0	.7	.7	.8	1.1
10	.71	.91	.2	1.6
20	1.02	1.31	.8	2
30	1.32	1.72	.4	3.1
40	1.62	2.13		3.9
50	1.86	2.43	.4	4.5
Weight				
BLX-II	45 LBS	54 LBS	68 LBS	96 LBS

BLX Features




BLX-II Mounting Options

Post Top Mount




Post Top fits over a 2" - 2-3/8" tenon and is adjustable up to 45 degrees.

Mast Arm Mount




Mast Arm Fitter fits over a 2" - 2-3/8" tenon.

Knuckle Mount




An adjustable knuckle slip fits over a 2-3/8" Tenon, and allows for up to 50 degrees of vertical adjustment in 10 degree increments from horizontal, as well as full side to side adjustment with the knuckle mount.

Bolt-On Arm Mount




The Bolt -On Arm (BOA) utilizes a 2 piece cleat system for easy installation. A Round Pole Plate Adaptor (RPP) is required for mounting to round poles.

Trunnion Mount



Trunnion Mount is adjustable up to 50 degrees.

Adjustable Wall Mount



Adjustable Wall Mount allows for up to 50 degrees of vertical adjustment in 10-degree increments.

WATTSTOPPER PLUS

FSP-600 Series

The FSP-600 series by Wattstopper PLUS is an integrated luminaire level lighting controller and sensor for indoor/outdoor lighting applications that require networked wireless control. The FSP-600 is designed to integrate directly into exterior, high bay, parking garage, and general site lighting solutions. It is a passive infrared (PIR) sensor and closed loop photosensor.

The FSP-600 series design intends to reduce installer labor time and make on-site start up easy for technicians.

Once commissioned and paired to a Wattstopper PLUS network, the devices can measure both motion and daylight contribution in order to automatically switch or dim lighting. It also provides the ability to communicate to other fixtures in the space without any front-end devices.

The Wattstopper PLUS FSP-600 series is available in a few different options including: internal, external straight nipple, and external drop nipple. Sensor lens options sold separately and should be ordered based on designed mounting height and desired finish.



FSP-621

FSP-200 Series

The FSP-200 series sensors provide multi-level control based on motion and/or daylight contribution. They control 0-10 VDC LED drivers or dimming ballasts, as well as non-dimming ballasts and, with an FSP-Lx Lens, are rated for wet and cold locations. All control parameters are adjustable via a wireless configuration tool capable of storing and transmitting sensor profiles. The FSP-200 series is available in two different voltage configurations adding flexibility to your fixture design or project.

Typically, the sensor ramps lighting On to the selected High mode level when motion is detected and the ambient light level is below the hold off setpoint. After the sensor stops detecting movement and the time delay elapses, lights fade to the Low mode level. If there is no motion during the subsequent cut off time delay, the lights will turn Off. For dusk to dawn control, the integral photocell can switch the lights On and Off based on the ambient light level so that lighting remains on overnight even without motion detection.

Initial setup and subsequent sensor adjustments are made using a Wireless Handheld Configuration Tool (FSIR-100). This tool enables adjustment of parameters including high and low modes, sensitivity, time delay, cut off and more. The FSIR-100 is also used to initiate automatic calibration of the FSP-2x1B ambient light level setpoint. The setpoint is used to hold the controlled lighting off or at a low level when there is sufficient daylight. The wireless tool stores up to six sensor parameter profiles to speed configuration of multiple sensors.



FSP-211




FSP-221


Lens with Shroud Dimensions

The FSP-Lx-S models include a shroud, which blocks high-angle light coming from the fixture, to improve photocell performance. With the shroud attached, the dimensions for all three lenses are identical


FSP-L2-S and FSP-L3-S





FSP-L7-S





COVERAGE



FSP-L2 top and side coverage patterns



FSP-L3 top and side coverage patterns



FSP-L7 top and side coverage patterns

BLXII LED SPECIFICATIONS / Forward Optics																																																																																																		
Led Count	Current & Watts	Distribution Type	27K												30K												70CRI												35K												40K												50K																																			
			Lumens	B	U	G	LPW	Lumens	B	U	G	LPW	Lumens	B	U	G	LPW	Lumens	B	U	G	LPW	Lumens	B	U	G	LPW	Lumens	B	U	G	LPW	Lumens	B	U	G	LPW																																																													
96LD	350 mA (98.6W)	T1	14611	4	0	4	148	15246	4	0	4	155	15246	4	0	4	155	15087	4	0	4	153	15881	4	0	4	161	15881	4	0	4	161	15881	4	0	4	161																																																													
		T2	14010	3	0	3	142	15229	3	0	3	154	15229	3	0	3	154	15148	3	0	3	154	15892	3	0	3	161	15892	3	0	3	161	15892	3	0	3	161																																																													
		T3R	13656	3	0	3	139	14843	3	0	3	151	14843	3	0	3	151	14765	3	0	3	150	15490	3	0	3	157	15490	3	0	3	157	15490	3	0	3	157																																																													
		T3	13484	2	0	2	137	14657	2	0	2	149	14657	2	0	2	149	14579	2	0	2	148	15296	2	0	2	155	15296	2	0	2	155	15296	2	0	2	155																																																													
		T3W	13812	2	0	3	140	15013	2	0	3	152	15013	2	0	3	152	14934	2	0	3	151	15668	2	0	3	159	15668	2	0	3	159	15668	2	0	3	159																																																													
		T3LG	13960	3	0	2	142	15173	3	0	3	154	15173	3	0	3	154	15043	3	0	3	153	15835	3	0	3	161	15835	3	0	3	161	15835	3	0	3	161																																																													
		T4	13688	3	0	3	139	14878	3	0	3	151	14878	3	0	3	151	14799	3	0	3	150	15526	3	0	3	157	15526	3	0	3	157	15526	3	0	3	157																																																													
		T4A	14579	2	0	2	148	15847	3	0	2	161	15847	3	0	2	161	15763	3	0	2	160	16538	3	0	2	168	16538	3	0	2	168	16538	3	0	2	168																																																													
		T4LG	13980	3	0	2	142	15196	3	0	2	154	15196	3	0	2	154	15065	3	0	2	153	15858	3	0	2	161	15858	3	0	2	161	15858	3	0	2	161																																																													
		T4FT	14754	2	0	3	150	15396	2	0	3	156	15396	2	0	3	156	15235	2	0	3	155	16037	3	0	3	163	16037	3	0	3	163	16037	3	0	3	163																																																													
		T5	14401	4	0	2	146	15653	4	0	2	159	15653	4	0	2	159	15570	4	0	2	158	16335	4	0	2	166	16335	4	0	2	166	16335	4	0	2	166																																																													
		T5LG	14056	3	0	2	143	15278	4	0	2	155	15278	4	0	2	155	15147	4	0	2	154	15944	4	0	2	162	15944	4	0	2	162	15944	4	0	2	162																																																													
		T5W	13246	4	0	3	134	14398	4	0	3	146	14398	4	0	3	146	14321	4	0	3	145	15025	4	0	3	152	15025	4	0	3	152	15025	4	0	3	152																																																													
		T5WW	12639	4	0	3	128	13738	4	0	3	139	13738	4	0	3	139	13665	4	0	3	139	14337	4	0	3	145	14337	4	0	3	145	14337	4	0	3	145																																																													
		FN	14368	4	0	1	146	15618	5	0	1	158	15618	5	0	1	158	15535	5	0	1	158	16298	5	0	1	165	16298	5	0	1	165	16298	5	0	1	165																																																													
		FM	14586	4	0	1	148	15854	5	0	1	161	15854	5	0	1	161	15770	5	0	1	160	16545	5	0	1	168	16545	5	0	1	168	16545	5	0	1	168																																																													
		FW	14978	3	0	1	152	15629	4	0	1	159	15629	4	0	1	159	15466	4	0	1	157	16280	4	0	1	165	16280	4	0	1	165	16280	4	0	1	165																																																													
96LD	530 mA (152.1W)	T1	22119	5	0	5	145	23080	5	0	5	152	23080	5	0	5	152	22840	5	0	5	150	24042	5	0	5	158	24042	5	0	5	158	24042	5	0	5	158																																																													
		T2	21210	3	0	4	139	23054	3	0	4	152	23054	3	0	4	152	22931	3	0	4	151	24059	4	0	4	158	24059	4	0	4	158	24059	4	0	4	158																																																													
		T3R	20673	3	0	4	136	22471	3	0	4	148	22471	3	0	4	148	22351	3	0	4	147	23450	3	0	4	154	23450	3	0	4	154	23450	3	0	4	154																																																													
		T3	20413	3	0	3	134	22189	3	0	3	146	22189	3	0	3	146	22071	3	0	3	145	23156	3	0	3	152	23156	3	0	3	152	23156	3	0	3	152																																																													
		T3W	20910	3	0	3	137	22728	3	0	3	149	22728	3	0	3	149	22607	3	0	3	149	23719	3	0	3	156	23719	3	0	3	156	23719	3	0	3	156																																																													
		T3LG	21133	3	0	3	139	22970	3	0	3	151	22970	3	0	3	151	22773	3	0	3	150	23971	3	0	3	158	23971	3	0	3	158	23971	3	0	3	158																																																													
		T4	20721	3	0	3	136	22523	3	0	3	148	22523	3	0	3	148	22403	3	0	3	147	23504	3	0	3	155	23504	3	0	3	155	23504	3	0	3	155																																																													
		T4A	22071	3	0	2	145	23990	3	0	3	158	23990	3	0	3	158	23863	3	0	3	157	25036	3	0	3	165	25036	3	0	3	165	25036	3	0	3	165																																																													
		T4LG	21164	3	0	3	139	23004	3	0	3	151	23004	3	0	3	151	22806	3	0	3	150	24007	3	0	3	158	24007	3	0	3	158	24007	3	0	3	158																																																													
		T4FT	22336	3	0	4	147	23307	3	0	4	153	23307	3	0	4	153	23064	3	0	4	152	24278	3	0	4	160	24278	3	0	4	160	24278	3	0	4	160																																																													
		T5	21800	4	0	2	143	23696	4	0	3	156	23696	4	0	3	156	23570	4	0	3	155	24729	4	0	3	163	24729	4	0	3	163	24729	4	0	3	163																																																													
		T5LG	21278	4	0	2	140	23129	4	0	2	152	23129	4	0	2	152	22930	4	0	2	151	24136	4	0	2	159	24136	4	0	2	159	24136	4	0	2	159																																																													
		T5W	20052	4	0	3	132	21796	4	0	4	143	21796	4	0	4	143	21680	4	0	4	143	22746	4	0	4	150	22746	4	0	4	150	22746	4	0	4	150																																																													
		T5WW	19134	4	0	3	126	20798	4	0	3	137	20798	4	0	3	137	20687	4	0	3	136	21704	4	0	4	143	21704	4	0	4	143	21704	4	0	4	143																																																													
		FN	21751	5	0	1	143	23643	5	0	1	155	23643	5	0	1	155	23517	5	0	1	155	24673	5	0	2	162	24673	5	0	2	162	24673	5	0	2	162																																																													
		FM	22081	5	0	1	145	24001	5	0	1	158	24001	5	0	1	158	23874	5	0	1	157	25047	5	0	1	165	25047	5	0	1	165	25047	5	0	1	165																																																													
		FW	22674	4	0	1	149	23660	4	0	1	156	23660	4	0	1	156	23414	4	0	1	154	24646	4	0	1	162	24646	4	0	1	162	24646	4	0	1	162																																																													
96LD	700 mA (203.8W)	T1	28660	5	0	5	141	29906	5	0	5	147	29906	5	0	5	147	29595	5	0	5	145	31152	5	0	5	153	31152	5	0	5	153	31152	5	0	5	153																																																													
		T2	27482	4	0	4	135	29672	4	0	4	147	29672	4	0	4	147	29713	4	0	4	146	31173	4	0	5	153	31173	4	0	5	153	31173	4	0	5	153																																																													
		T3R	26787	4	0	4	131	29116	4	0	4	143	29116	4	0	4	143	28961	4	0	4	142	30385	4	0	4	149	30385	4	0	4	149	30385	4	0	4	149																																																													
		T3	26450	3	0	3	130	28750	3	0	4	141	28750	3	0	4	141	28598	3	0	4	140	30003	3	0	4	147	30003	3	0	4	147	30003	3	0	4	147																																																													
		T3W	27094	3	0	4	133	29450	3	0	4	144	29450	3	0	4	144	29293	3	0	4	144	30733	3	0	4	151	30733	3	0	4	151	30733	3	0	4	151																																																													
		T3LG	27362	3	0	3	134	29763	4	0	3	146	29763	4	0	3	146	29507	4	0	3	145	31060	4	0	4	152	31060	4	0	4	152	31060	4	0	4	152																																																													
		T4	26849	4	0	4	132	29184	4	0	4	143	29184	4	0	4	143	29029	4	0	4	142	30456	4	0	4	149	30456	4	0	4	149	30456	4	0	4	149																																																													
		T4A																																																																																																

BLX-II LED SPECIFICATIONS / Forward Optics																											
Led Count	Current & Watts	Distribution Type	70CRI																								
			27K					30K					35K					40K					50K				
			Lumens	B	U	G	LPW	Lumens	B	U	G	LPW	Lumens	B	U	G	LPW	Lumens	B	U	G	LPW	Lumens	B	U	G	LPW
128LD	350 mA (131.5W)	T1	19288	4	0	4	147	20127	4	0	4	153	20127	4	0	4	153	19917	4	0	4	152	20966	4	0	4	159
		T2	18495	3	0	3	141	20104	3	0	3	153	20104	3	0	3	153	19997	3	0	3	152	20980	3	0	4	160
		T3R	18028	3	0	3	137	19595	3	0	3	149	19595	3	0	3	149	19491	3	0	3	148	20449	3	0	3	156
		T3	17801	3	0	3	135	19349	3	0	3	147	19349	3	0	3	147	19246	3	0	3	146	20192	3	0	3	154
		T3W	18234	3	0	3	139	19620	3	0	3	151	19620	3	0	3	151	19714	3	0	3	150	20683	3	0	3	157
		T3LG	18428	3	0	3	140	20031	3	0	3	152	20031	3	0	3	152	19859	3	0	3	151	20904	3	0	3	159
		T4	18070	3	0	3	137	19641	3	0	3	149	19641	3	0	3	149	19536	3	0	3	149	20497	3	0	3	156
		T4A	19247	3	0	2	146	20920	3	0	2	159	20920	3	0	2	159	20809	3	0	2	158	21832	3	0	2	166
		T4LG	18456	3	0	2	140	20060	3	0	3	153	20060	3	0	3	153	19888	3	0	2	151	20935	3	0	3	159
		T4FT	19478	3	0	3	148	20324	3	0	4	155	20324	3	0	4	155	20113	3	0	4	153	21171	3	0	4	161
		T5	19011	4	0	2	145	20664	4	0	2	157	20664	4	0	2	157	20554	4	0	2	156	21564	4	0	2	164
		T5LG	18555	4	0	2	141	20169	4	0	2	153	20169	4	0	2	153	19995	4	0	2	152	21048	4	0	2	160
		T5W	17486	4	0	3	133	19007	4	0	3	145	19007	4	0	3	145	18906	4	0	3	144	19835	4	0	3	151
		T5WW	16686	4	0	3	127	18137	4	0	3	138	18137	4	0	3	138	18040	4	0	3	137	18927	4	0	3	144
		FN	18968	5	0	1	144	20617	5	0	1	157	20617	5	0	1	157	20508	5	0	1	156	21516	5	0	1	164
		FM	19256	5	0	1	146	20930	5	0	1	159	20930	5	0	1	159	20819	5	0	1	158	21842	5	0	1	166
		FW	19773	4	0	1	150	20632	4	0	1	157	20632	4	0	1	157	20417	4	0	1	155	21492	4	0	1	163
128LD	530 mA (202.8W)	T1	29200	5	0	5	144	30469	5	0	5	150	30469	5	0	5	150	30152	5	0	5	149	31739	5	0	5	157
		T2	27999	4	0	4	138	30434	4	0	4	150	30434	4	0	4	150	30272	4	0	4	149	31760	4	0	5	157
		T3R	27291	4	0	4	135	29664	4	0	4	146	29664	4	0	4	146	29507	4	0	4	146	30957	4	0	5	153
		T3	26948	3	0	3	133	29292	3	0	4	144	29292	3	0	4	144	29136	3	0	4	144	30568	3	0	4	151
		T3W	27604	3	0	4	136	30004	3	0	4	148	30004	3	0	4	148	29845	3	0	4	147	31312	3	0	4	154
		T3LG	27898	4	0	3	138	30324	4	0	3	150	30324	4	0	3	150	30063	4	0	3	148	31645	4	0	4	156
		T4	27355	4	0	4	135	29733	4	0	4	147	29733	4	0	4	147	29575	4	0	4	146	31029	4	0	4	153
		T4A	29137	3	0	3	144	31671	3	0	3	156	31671	3	0	3	156	31502	3	0	3	155	33051	3	0	3	163
		T4LG	27939	3	0	3	138	30369	3	0	3	150	30369	3	0	3	150	30107	3	0	3	148	31692	3	0	3	156
		T4FT	29486	3	0	4	145	30768	3	0	5	152	30768	3	0	5	152	30448	3	0	5	150	32050	3	0	5	158
		T5	28779	5	0	3	142	31282	5	0	3	154	31282	5	0	3	154	31115	5	0	3	153	32645	5	0	3	161
		T5LG	28090	4	0	3	139	30533	5	0	3	151	30533	5	0	3	151	30270	5	0	3	149	31863	5	0	3	157
		T5W	26471	5	0	4	131	28773	5	0	4	142	28773	5	0	4	142	28620	5	0	4	141	30027	5	0	4	148
		T5WW	25260	5	0	4	125	27456	5	0	4	135	27456	5	0	4	135	27310	5	0	4	135	28653	5	0	4	141
		FN	28715	5	0	2	142	31212	5	0	2	154	31212	5	0	2	154	31046	5	0	2	153	32572	5	0	2	161
		FM	29150	5	0	1	144	31685	5	0	2	156	31685	5	0	2	156	31516	5	0	2	155	33066	5	0	2	163
		FW	29933	5	0	1	148	31234	5	0	1	154	31234	5	0	1	154	30909	5	0	1	152	32536	5	0	1	160
128LD	700 mA (271.8W)	T1	37835	5	0	5	139	39480	5	0	5	145	39480	5	0	5	145	39069	5	0	5	144	41125	5	0	5	151
		T2	36280	4	0	5	133	39434	4	0	5	145	39434	4	0	5	145	39225	4	0	5	144	41153	4	0	5	151
		T3R	35362	4	0	5	130	38437	4	0	5	141	38437	4	0	5	141	38233	4	0	5	141	40112	4	0	5	148
		T3	34918	3	0	4	128	37954	3	0	4	140	37954	3	0	4	140	37753	3	0	4	139	39608	3	0	4	146
		T3W	35767	3	0	4	132	38877	3	0	4	143	38877	3	0	4	143	38671	3	0	4	142	40572	3	0	5	149
		T3LG	36148	4	0	4	133	39292	4	0	4	145	39292	4	0	4	145	38954	4	0	4	143	41004	4	0	4	151
		T4	35444	4	0	4	130	38526	4	0	5	142	38526	4	0	5	142	38321	4	0	5	141	40205	4	0	5	148
		T4A	37754	3	0	3	139	41037	4	0	3	151	41037	4	0	3	151	40818	4	0	3	150	42825	4	0	3	158
		T4LG	36202	4	0	4	133	39350	4	0	4	145	39350	4	0	4	145	39011	4	0	4	144	41064	4	0	4	151
		T4FT	38206	3	0	5	141	39867	4	0	5	147	39867	4	0	5	147	39452	4	0	5	145	41528	4	0	5	153
		T5	37290	5	0	4	137	40533	5	0	4	149	40533	5	0	4	149	40317	5	0	4	148	42299	5	0	4	156
		T5LG	36397	5	0	3	134	39562	5	0	3	146	39562	5	0	3	146	39222	5	0	3	144	41286	5	0	3	152
		T5W	34300	5	0	5	126	37283	5	0	5	137	37283	5	0	5	137	37084	5	0	5	136	38907	5	0	5	143
		T5WW	32730	5	0	5	120	35576	5	0	5	131	35576	5	0	5	131	35386	5	0	5	130	37126	5	0	5	137
		FN	37207	5	0	2	137	40442	5	0	2	149	40442	5	0	2	149	40227	5	0	2	148	42204	5	0	2	155
		FM	37771	5	0	2	139	41055	5	0	2	151	41055	5	0	2	151	40837	5	0	2	150	42844	5	0	2	158
		FW	38785	5	0	2	143	40471	5	0	2	149	40471	5	0	2	149	40050	5	0	2	147	42158	5	0	2	155
128LD	1050 mA (419.2W)	T1	53444	5	0	5	128	55873	5	0	5	133	55873	5	0	5	133	55291	5	0	5	132	58201	5	0	5	139
		T2	51343	5	0	5	122	55808	5	0	5	133	55808	5	0	5	133	55511	5	0	5	132	58240	5	0	5	139
		T3R	50045	4	0	5	119	54397	5	0	5	130	54397	5	0	5	130	54108	5	0	5	129	56767	5	0	5	135
		T3	49416	4	0	5	118	53713	4	0	5	128	53713	4	0	5	128	53428	4	0	5	127	56054	4	0	5	134
		T3W	50618	4	0	5	121	55020	4	0	5	131	55020	4	0	5	131	54727	4	0	5	131	57417	4	0	5	137
		T3LG	51158	4	0	5	122	55606	5	0	5	133	55606	5	0	5	133	55128	5	0	5	132	58029	5	0	5	

BLX-II LED SPECIFICATIONS / Forward Optics																											
Led Count	Current & Watts	Distribution Type																									
			27K					30K					70CRI 35K					40K					50K				
			Lumens	B	U	G	LPW	Lumens	B	U	G	LPW	Lumens	B	U	G	LPW	Lumens	B	U	G	LPW	Lumens	B	U	G	LPW
192LD	350 mA (197.2W)	T1	28354	5	0	5	144	29587	5	0	5	150	29587	5	0	5	150	29278	5	0	5	148	30819	5	0	5	156
		T2	27188	4	0	4	138	29553	4	0	4	150	29553	4	0	4	150	29395	4	0	4	149	30840	4	0	5	156
		T3R	26501	4	0	4	134	28805	4	0	4	146	28805	4	0	4	146	28652	4	0	4	145	30060	4	0	4	152
		T3	26168	3	0	3	133	28443	3	0	4	144	28443	3	0	4	144	28292	3	0	4	143	29683	3	0	4	151
		T3W	26804	3	0	4	136	29135	3	0	4	148	29135	3	0	4	148	28980	3	0	4	147	30405	3	0	4	154
		T3LG	27090	3	0	3	137	29445	4	0	3	149	29445	4	0	3	149	29192	4	0	3	148	30729	4	0	4	156
		T4	26562	4	0	4	135	28872	4	0	4	146	28872	4	0	4	146	28718	4	0	4	146	30130	4	0	4	153
		T4A	26293	3	0	3	143	30753	3	0	3	156	30753	3	0	3	156	30590	3	0	3	155	32093	3	0	3	163
		T4LG	27130	3	0	3	138	29489	3	0	3	150	29489	3	0	3	150	29235	3	0	3	148	30774	3	0	3	156
		T4FT	28632	3	0	4	145	29877	3	0	5	152	29877	3	0	5	152	29566	3	0	4	150	31122	3	0	5	158
		T5	27946	5	0	3	142	30376	5	0	3	154	30376	5	0	3	154	30214	5	0	3	153	31699	5	0	3	161
		T5LG	27276	4	0	2	138	29648	5	0	3	150	29648	5	0	3	150	29393	4	0	3	149	30940	5	0	3	157
		T5W	25705	5	0	4	130	27940	5	0	4	142	27940	5	0	4	142	27791	5	0	4	141	29157	5	0	4	148
		T5WW	24528	5	0	4	124	26661	5	0	4	135	26661	5	0	4	135	26519	5	0	4	134	27823	5	0	4	141
		FN	27883	5	0	2	141	30308	5	0	2	154	30308	5	0	2	154	30146	5	0	2	153	31628	5	0	2	160
		FM	28306	5	0	1	144	30767	5	0	1	156	30767	5	0	1	156	30603	5	0	1	155	32108	5	0	2	163
		FW	29066	5	0	1	147	30330	5	0	1	154	30330	5	0	1	154	30014	5	0	1	152	31593	5	0	1	160
192LD	530 mA (304.1W)	T1	42924	5	0	5	141	44790	5	0	5	147	44790	5	0	5	147	44323	5	0	5	146	46656	5	0	5	153
		T2	41159	4	0	5	135	44738	4	0	5	147	44738	4	0	5	147	44500	4	0	5	146	46688	4	0	5	154
		T3R	40118	4	0	5	132	43607	4	0	5	143	43607	4	0	5	143	43375	4	0	5	143	45507	4	0	5	150
		T3	39614	3	0	4	130	43059	4	0	4	142	43059	4	0	4	142	42830	4	0	4	141	44935	4	0	5	148
		T3W	40578	3	0	5	133	44106	4	0	5	145	44106	4	0	5	145	43872	4	0	5	144	46028	4	0	5	151
		T3LG	41010	4	0	4	135	44576	4	0	4	147	44576	4	0	4	147	44193	4	0	4	145	46519	4	0	4	153
		T4	40211	4	0	5	132	43708	4	0	5	144	43708	4	0	5	144	43475	4	0	5	143	45613	4	0	5	150
		T4A	42831	4	0	3	141	46556	4	0	3	153	46556	4	0	3	153	46308	4	0	3	152	48585	4	0	3	160
		T4LG	41071	4	0	4	135	44642	4	0	4	147	44642	4	0	4	147	44258	4	0	4	146	46587	4	0	4	153
		T4FT	43345	4	0	5	143	45229	4	0	5	149	45229	4	0	5	149	44758	4	0	5	147	47114	4	0	5	155
		T5	42305	5	0	4	139	45984	5	0	4	151	45984	5	0	4	151	45740	5	0	4	150	47988	5	0	4	158
		T5LG	41292	5	0	3	136	44883	5	0	4	148	44883	5	0	4	148	44497	5	0	4	146	46839	5	0	4	154
		T5W	38913	5	0	5	128	42297	5	0	5	139	42297	5	0	5	139	42072	5	0	5	138	44140	5	0	5	145
		T5WW	37132	5	0	5	122	40360	5	0	5	133	40360	5	0	5	133	40146	5	0	5	132	42119	5	0	5	138
		FN	42211	5	0	2	139	45881	5	0	2	151	45881	5	0	2	151	45637	5	0	2	150	47881	5	0	2	157
		FM	42851	5	0	2	141	46577	5	0	2	153	46577	5	0	2	153	46329	5	0	2	152	48607	5	0	2	160
		FW	44001	5	0	2	145	45914	5	0	2	151	45914	5	0	2	151	45436	5	0	2	149	47828	5	0	2	157
192LD	700 mA (407.7 W)	T1	55617	5	0	5	136	58036	5	0	5	142	58036	5	0	5	142	57431	5	0	5	141	60454	5	0	5	148
		T2	53331	5	0	5	131	57969	5	0	5	142	57969	5	0	5	142	57660	5	0	5	141	60495	5	0	5	148
		T3R	51983	5	0	5	128	56503	5	0	5	139	56503	5	0	5	139	56202	5	0	5	138	58965	5	0	5	145
		T3	51330	4	0	5	126	55793	4	0	5	137	55793	4	0	5	137	55496	4	0	5	136	58224	4	0	5	143
		T3W	52578	4	0	5	129	57150	4	0	5	140	57150	4	0	5	140	56846	4	0	5	139	59640	4	0	5	146
		T3LG	53138	5	0	5	130	57759	5	0	5	142	57759	5	0	5	142	57262	5	0	5	140	60276	5	0	5	148
		T4	52103	4	0	5	128	56634	5	0	5	139	56634	5	0	5	139	56333	5	0	5	138	59102	5	0	5	145
		T4A	55498	4	0	4	136	60324	4	0	4	148	60324	4	0	4	148	60003	4	0	4	147	62953	4	0	4	154
		T4LG	53216	4	0	4	131	57844	5	0	5	142	57844	5	0	5	142	57347	5	0	5	141	60365	5	0	5	148
		T4FT	56163	4	0	5	138	58605	4	0	5	144	58605	4	0	5	144	57994	4	0	5	142	61047	4	0	5	150
		T5	54817	5	0	4	134	59583	5	0	5	146	59583	5	0	5	146	59266	5	0	5	145	62180	5	0	5	153
		T5LG	53504	5	0	4	131	58156	5	0	4	143	58156	5	0	4	143	57656	5	0	4	141	60691	5	0	4	149
		T5W	50421	5	0	5	124	54805	5	0	5	134	54805	5	0	5	134	54514	5	0	5	134	57194	5	0	5	140
		T5WW	48113	5	0	5	118	52296	5	0	5	128	52296	5	0	5	128	52018	5	0	5	128	54575	5	0	5	134
		FN	54894	5	0	2	134	59450	5	0	3	146	59450	5	0	3	146	59134	5	0	3	145	62041	5	0	3	152
		FM	55523	5	0	2	136	60351	5	0	2	148	60351	5	0	2	148	60030	5	0	2	147	62981	5	0	2	154
		FW	57014	5	0	2	140	59493	5	0	2	146	59493	5	0	2	146	58873	5	0	2	144	61972	5	0	2	152
192LD	1050 mA (628.8W)	T1	78710	5	0	5	125	82133	5	0	5	131	82133	5	0	5	131	81277	5	0	5	129	85555	5	0	5	136
		T2	75475	5	0	5	120	82038	5	0	5	130	82038	5	0	5	130	81602	5	0	5	130	85613	5	0	5	136
		T3R	73566	5	0	5	117	79963	5	0	5	127	79963	5	0	5	127	79538	5	0	5	126	83448	5	0	5	133
		T3	72842	5	0	5	116	78959	5	0	5	126	78959	5	0	5	126	78539	5	0	5	125	82400	5	0	5	131
		T3W	74409	4	0	5	118	80879	5	0	5	129	80879	5	0	5	129	80449	5	0	5	128	84404	5	0	5	134
		T3LG	75202	5	0	5	120	81741	5	0	5	130	81741	5	0	5	130	81038	5	0	5	129	85303	5	0	5	

BLX-II LED SPECIFICATIONS / Forward Optics																																																		
Led Count	Current & Watts	Distribution Type	27K												30K												70CRI								40K								50K							
			Lumens	B	U	G	LPW	Lumens	B	U	G	LPW	Lumens	B	U	G	LPW	Lumens	B	U	G	LPW	Lumens	B	U	G	LPW	Lumens	B	U	G	LPW																		
256LD	350 mA (262.9W)	T1	37034	5	0	5	141	38644	5	0	5	147	38644	5	0	5	147	38241	5	0	5	145	40254	5	0	5	153																							
		T2	35511	4	0	5	135	38599	4	0	5	147	38599	4	0	5	147	38394	4	0	5	146	40281	4	0	5	153																							
		T3R	34613	4	0	5	132	37623	4	0	5	143	37623	4	0	5	143	37423	4	0	5	142	39263	4	0	5	149																							
		T3	34178	3	0	4	130	37150	3	0	4	141	37150	3	0	4	141	36953	3	0	4	141	38789	3	0	4	147																							
		T3W	35010	3	0	4	133	38054	3	0	4	145	38054	3	0	4	145	37851	3	0	4	144	39712	3	0	4	151																							
		T3LG	35383	4	0	4	135	38459	4	0	4	146	38459	4	0	4	146	38129	4	0	4	145	40135	4	0	4	153																							
		T4	34693	4	0	4	132	37710	4	0	5	143	37710	4	0	5	143	37510	4	0	5	143	39354	4	0	5	150																							
		T4A	36954	3	0	3	141	40167	4	0	3	153	40167	4	0	3	153	39954	4	0	3	152	41918	4	0	3	159																							
		T4LG	35435	4	0	4	135	38516	4	0	4	146	38516	4	0	4	146	38185	4	0	4	145	40195	4	0	4	153																							
		T4FT	37397	3	0	5	142	39023	3	0	5	148	39023	3	0	5	148	38616	3	0	5	147	40649	4	0	5	155																							
		T5	36500	5	0	3	139	39674	5	0	4	151	39674	5	0	4	151	39463	5	0	4	150	41403	5	0	4	157																							
		T5LG	35626	5	0	3	135	38724	5	0	3	147	38724	5	0	3	147	38391	5	0	3	146	40412	5	0	3	154																							
		T5W	33573	5	0	5	128	36493	5	0	5	139	36493	5	0	5	139	36299	5	0	5	138	38083	5	0	5	145																							
		T5WW	32036	5	0	4	122	34822	5	0	5	132	34822	5	0	5	132	34637	5	0	5	132	36340	5	0	5	138																							
		FN	36419	5	0	2	139	39585	5	0	2	151	39585	5	0	2	151	39375	5	0	2	150	41310	5	0	2	157																							
		FM	36971	5	0	2	141	40186	5	0	2	153	40186	5	0	2	153	39972	5	0	2	152	41937	5	0	2	159																							
		FW	37963	5	0	2	144	39614	5	0	2	151	39614	5	0	2	151	39201	5	0	2	149	41265	5	0	2	157																							
		256LD	530 mA (405.5W)	T1	56063	5	0	5	1																																									